FORD (EU) ESCORT ESCORT 1.6 DIESEL (1984-1990)



ENGINE LTA Capacity: 5 liter, Filter capacity: 0,5 liter					
use Normal		CLIMATE			
		Mediterranean			
PRODUCT RECOMMENDATION 1					
Bi-Turbo 20W-50					
Change every 10000 km/ 6 months					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Emperol 5W-50	Asyntho 5W-30	Emperol 10W-40			

Change every 10000 km/ 6 months

TRANSAXLE MANUAL 5/1 Capacity: 3,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Chack over 20000 km/ 12 months	:	·

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change aver (COOOO km/ 20 magnitus	1	5

Change every 60000 km/ 36 months

COOLING SYSTEM Capacity: 9,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant -38 Organic NF		
Change every 24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.