## FORD (EU) ESCORT ESCORT 1.6 (1989-1993)



<b>ENGINE</b> CVH, L Capacity: 3,5 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 3000 km, change every 1000	00 km/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	Bi-Turbo 15W-40	
Check every 3000 km, change every 1000	00 km/ 12 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Check every 3000 km, change every 1000	00 km/ 12 months	

TRANSAXLE AUTOMATIC CTX Capacity: 3,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4016	ATF Dexron II-D		
Check every 20000 km/24 months	, change every 40000 km/ 48 months	'	

TRANSAXLE MANUAL 5/1 Capacity: 3,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 20000 km/24 months		

## FORD (EU) ESCORT ESCORT 1.6 (1989-1993)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 60000 km/ 36 months		·

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	ATF Dexron II-D	

Check every 10000 km/ 12 months

COOLING SYSTEM Capacity: 7,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant -38 Organic NF	
Change every 60000 km/24 month	78	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.