

# FORD (EU) FIESTA MK VI FIESTA 1.0 (48 KW) (2012-2017)

**ENGINE** XMJA/XMJB/XMJC/XMJD

Capacity: 4,65 liter (Initial fill), Capacity: 4,1-4,6 liter (Service fill), Filter capacity: 0,1-0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Duranza ECO 5W-20</b>		

**TRANSAXLE MANUAL** iB5 5/1

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 1081</b>		

*Check every 20000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-LV Super DOT 4</b>		

*Change every 24 months***COOLING SYSTEM**

Capacity: 5,8-6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 40000 km/ 12 months, change every 120 months***AIRCONDITIONING COMPRESSOR**

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*