

FORD (EU) FOCUS MK II FOCUS 1.6 16V (74 KW) (2004-2011)



ENGINE Duratec-16V
Capacity: 4,1 liter, Filter capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza ECO 5W-20	Duranza LSP 5W-30

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC 4F27E 4/1
Capacity: 6,7 liter (+ cooler)

USE	CLIMATE
->07/2007	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 2032	

Check every 20000 km/ 12 months, change every 120000 km/ 72 months

USE	CLIMATE
08/2007 ->	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 4036	SP Matic 2032

Check every 20000 km/ 12 months, change every 120000 km/ 72 months

TRANSAXLE MANUAL iB5 5/1
Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Check every 20000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 20000 km, change every 24 months

FORD (EU) FOCUS MK II FOCUS 1.6 16V (74 KW) (2004-2011)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 2000 km/ 12 months

COOLING SYSTEM

Capacity: 5,5 liter, Capacity: 5,8 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.