

FORD (EU) FOCUS MK III (C346) FOCUS 2.0 TDCI DURATORQ (103 KW) (2011-2014)

**ENGINE** UFDB Duratorq

Capacity: 6,45 liter (Dry fill), Capacity: 5,65 liter (Service fill), Filter capacity: 0,27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza LSP 5W-30***Change every 15000 km/ 12 months***TRANSAXLE MANUAL** MMT6 6/1

Capacity: 1,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 15000 km/ 12 months***TRANSAXLE MANUAL** MTX75 5/1

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 15000 km/ 12 months***TRANSAXLE SEMI-AUTOMATIC** DPS6/6DCT250 (PowerShift) 6/1

Capacity: 1,8 liter (Dry fill), Capacity: 1,7 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 15000 km/ 12 months***TRANSAXLE SEMI-AUTOMATIC** MPS6/6DCT450 (PowerShift) 6/1

Capacity: 6-7,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2072***Change every 60000 km/ 36 months*

FORD (EU) FOCUS MK III (C346) FOCUS 2.0 TDCI DURATORQ (103 KW) (2011-2014)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
<i>Change every 24 months</i>		

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 40000 km/ 24 months, change every 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 515-545 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.