FORD (EU) FUSION FUSION 1.4 TDCI (2002-2012)



ENGINE F6JA/F6JD Capacity: 4,2 liter (Initial fill), Capacity: 3,8 liter (Service fill), Filter capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AW81-40 4/ Capacity: 5,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

TRANSAXLE MANUAL 5/1 Capacity: 2,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

HYDRAULIC BRAKE/CLUTCH SYSTI Capacity: 0-0 liter (Between min and m			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months			

POWER STEERING Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

FORD (EU) FUSION FUSION 1.4 TDCI (2002-2012)



COOLING SYSTEM Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 120 months	'	

AIRCONDITIONING COMPRESSOR

Capacity: 207 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 467-663 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.