## FORD (EU) GALAXY MK III (WA6) GALAXY 1.8 TDCI DURATORQ (92 KW) (2006-2008)



<b>ENGINE</b> QYWA Capacity: 6,1 liter (Initial fill), Capacity: 5,6	liter (Service fill), Filter capacity: 0,6 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
Change every 20000 km/ 12 months		

TRANSAXLE MANUAL MTX75 5/1
Capacity: 1,9 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
SP Gear 1011 Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 40000 km/24 months	·

COOLING SYSTEM Capacity: 7,93 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 40000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.