

FORD (EU) MAVERICK / ESCAPE

MAVERICK / ESCAPE 2.3 16V (2004-2007)

**ENGINE** Duratec-HE

Capacity: 4,25 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Change every 20000 km/ 12 months***DIFFERENTIAL REAR** (4x4)

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 15000 km/ 12 months, change every 150000 km***TRANSAXLE AUTOMATIC** 4/1

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032**TRANSAXLE MANUAL** (4x4) 5/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 15000 km/ 12 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL** 5/1

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 15000 km/ 12 months, change every 90000 km/ 72 months*

FORD (EU) MAVERICK / ESCAPE

MAVERICK / ESCAPE 2.3 16V (2004-2007)



TRANSFERBOX AUTOMATIC GEARBOX (4X4)

Capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Check every 15000 km/ 12 months

TRANSFERBOX MANUAL GEARBOX (4X4)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

Check every 15000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

PRODUCT RECOMMENDATION 2

Coolant SP 11

Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.