## FORD (EU) MONDEO MK IV MONDEO 2.2 TDCI DURATORQ (2008-2010)



ENGINE Q4BA (DW12) Capacity: 6,5 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,6 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1					
Duranza LSP 5W-30					
Change every 20000 km/ 12 months		•			

TRANSAXLE AUTOMATIC AWF21 6/1 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

TRANSAXLE MANUAL MMT6 6/1 Capacity: 1,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
Check every 20000 km/ 12 months	

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months	·	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 20000 km/ 12 months	

## FORD (EU) MONDEO MK IV MONDEO 2.2 TDCI DURATORQ (2008-2010)



COOLING SYSTEM Capacity: 8,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 20000 km/ 12 months	c, change every 120 months	<u> </u>

- Check every 20000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.