

FORD (EU) S-MAX MK I S-MAX 2.0 16V (2010-2013)**ENGINE** AOWB M14 Duratec-HE

Capacity: 4,6 liter (Initial fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza ECO 5W-20	Duranza LSP 5W-30

*Change every 20000 km/ 12 months***TRANSAXLE MANUAL** MTX75 5/1

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 1081	

HYDRAULIC BRAKE SYSTEM FROM 04/2012 ONWARDS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

*Change every 24 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

*Change every 24 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

FORD (EU) S-MAX MK I S-MAX 2.0 16V (2010-2013)**COOLING SYSTEM**

Capacity: 6,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Change every 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.