## FORD (EU) S-MAX MK I S-MAX 2.2 TDCI DURATORQ (147 KW) (2010-2012)



ENGINE KNWA Duratorq Capacity: 6,5 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
Change every 20000 km/ 12 months		

TRANSAXLE AUTOMATIC AWF21 6/1 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

TRANSAXLE MANUAL M66 6/1 Capacity: 2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
	:

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change aven 21 months		

Change every 24 months

POWER STEERING	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 SP Fluid 3013	

## FORD (EU) S-MAX MK I S-MAX 2.2 TDCI DURATORQ (147 KW) (2010-2012)



COOLING SYSTEM Capacity: 8,14 liter (+ heater)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 200 CM3, Capacity: 250 CM3 (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 835-865 grams (With auxiliary climate control), Filter capacity: 585-615 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.