

FORD (USA) ESCAPE, 3. GEN C1 ESCAPE 2.5 16V (2013-2016)



MOTOR Duratec 25
Kapacitet: 5,4 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 10000 mil/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 5000 mil/ 6 måneder

TRANSAKSEL AUTOMATISK

Kapacitet: 8,5 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Skift alle 150000 mil

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Skift alle 30000 mil/ 3 måneder

HYDRAULISK BREMSESYSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

FORD (USA) ESCAPE, 3. GEN C1 ESCAPE 2.5 16V (2013-2016)



KØLESYSTEM

Kapacitet: 8,7-9,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15

PRODUKTANBEFALING 2

Coolant SP 15+

Kontroller alle 6 måneder, skift alle 80000 km/ 36 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15

PRODUKTANBEFALING 2

Coolant SP 15+

Kontroller alle 6 måneder, skift alle 160000 km/ 72 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 133 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 760 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.