

FORD (USA) EXPEDITION EXPEDITION 5.4

V8 AWD (2005-2006)

**ENGINE**

Capacity: 6,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 5000 miles***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 3000 miles/ 3 months/ 200 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,8-2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Change every 150000 miles***DIFFERENTIAL REAR**

Capacity: 2,13 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140***Change every 150000 miles***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140***Change every 150000 miles*

FORD (USA) EXPEDITION EXPEDITION 5.4

V8 AWD (2005-2006)

**TRANSFERBOX**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Change every 60000 miles***TRANSMISSION AUTOMATIC 4R75E 4/1**

Capacity: 13,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 15000 miles, change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Check every 15000 miles, change every 30000 miles***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

*Check every 12 months, change every 24 months***POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 8000 km

FORD (USA) EXPEDITION EXPEDITION 5.4 V8 AWD (2005-2006)



COOLING SYSTEM

Capacity: 19,4 liter, Capacity: 19,7 liter (Heavy Duty), Capacity: 20,9 liter (Heavy Duty + additional heater), Capacity: 20,7 liter (with 4 zone airconditioning system)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

PRODUCT RECOMMENDATION 2

Coolant SP 11

Check every 12 months, change every 240000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.