## FORD (USA) EXPLORER EXPLORER 3.5 TI-VCT V6 (2012-2016)



ENGINE Ti-VCT Capacity: 5,7 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 5	000 miles	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 1	0000 miles/ 12 months	

TRANSAXLE AUTOMATIC 6F50 6/1 Capacity: 10,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 150000 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Change every	30000 miles/ 3 i	months		

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4036	SP Matic 2032		
Change every 150000 miles			
USE		CLIMATE	
		Moderate	
Severe			
Severe PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		

## FORD (USA) EXPLORER EXPLORER 3.5 TI-VCT V6 (2012-2016)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

COOLING SYSTEM Capacity: 11,5 liter		
USE		CLIMATE
First change only, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Change every 100000 miles/72 mg	onths	
USE		CLIMATE
Normal, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Change every 50000 miles/ 36 mor	nths	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.