

FORD (USA) EXPLORER EXPLORER 4.0 V6 (2006-2010)

**ENGINE**

Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 5000 miles/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

*Change every 3000 miles/ 3 months/ 200 hours***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 12 months, change every 100000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

*Change every 50000 miles***TRANSMISSION AUTOMATIC 5R55S 5/1**

Capacity: 11,7 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 150000 miles

FORD (USA) EXPLORER EXPLORER 4.0 V6 (2006-2010)


TRANSMISSION AUTOMATIC 6R60 (ZF 6HP26) 6/1

Capacity: 11,6 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 150000 miles*
HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 12 months, change every 24 months*
POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 6 months*
GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 5000 miles*

FORD (USA) EXPLORER EXPLORER 4.0 V6 (2006-2010)

**COOLING SYSTEM**

Capacity: 11,5 liter, Capacity: 13,2 liter (with 4 zone airconditioning system)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 100000 miles/ 60 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 50000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.