## FORD (USA) FUSION FUSION 2.5 (2013-2015)



ENGINE Duratec 25 Capacity: 5,4 liter		
use Flexible (max)		сымате Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Charles war demonstration and the second state of the second se		

Check every 1 months, change every 10000 miles/ 12 months

<b>TRANSAXLE AUTOMATIC</b> 6/1 Capacity: 8,5 liter (Dry fill)		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 30000 miles/ 3 months		

use Flexible (max)		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
01 (50000 ''		

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change aver 21 manths	

Change every 24 months

## FORD (USA) FUSION FUSION 2.5 (2013-2015)



COOLING SYSTEM Capacity: 6,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 50000 miles			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 100000 miles			

## AIRCONDITIONING

Capacity: 560-680 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR Capacity: 154 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.