

FORD (USA) FUSION FUSION 3.5 V6 AWD (2010-2011)



ENGINE Duratec 35
Capacity: 5,2 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 10000 miles/ 12 months

DIFFERENTIAL REAR
Capacity: 1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

TRANSAXLE AUTOMATIC 6F35 6/1
Capacity: 8,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032

Change every 150000 miles

TRANSAXLE AUTOMATIC Aisin Warner F21 6/1
Capacity: 7 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 150000 miles

TRANSAXLE MANUAL
Capacity: 2,87 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Change every 150000 miles

FORD (USA) FUSION FUSION 3.5 V6 AWD (2010-2011)



TRANSFERBOX

Capacity: 0,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM

Capacity: 10,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 50000 miles/ 36 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 100000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.