

FORD (USA) FUSION FUSION 3.0 V6 24V (2005-2009)



MOTOR Duratec
Kapacitet: 5,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Skift alle 8000 km

TRANSAKSEL AUTOMATISK 6/1
Kapacitet: 7,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 48000 km, skift alle 240000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 24 måneder

SERVOSTYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

ATF Dexron II-D

FORD (USA) FUSION FUSION 3.0 V6 24V (2005-2009)



KØLESYSTEM

Kapacitet: 9,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 11

Skift alle 80000 km/ 36 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 11

Skift alle 150000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.