

FORD (USA) MUSTANG, 5TH GEN

MUSTANG SHELBY GT500 (2011-2012)



ENGINE Ti-VCT
Capacity: 6,1 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-50

Change every 10000 miles/ 12 months

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

TRANSMISSION MANUAL Tremec TR-6060 6/1

Capacity: 3,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Change every 150000 miles

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

FORD (USA) MUSTANG, 5TH GEN

MUSTANG SHELBY GT500 (2011-2012)

**COOLING SYSTEM**

Capacity: 20 liter, Capacity: 3,95 liter (intercooler)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 45000 miles/ 36 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.