

GMC (USA / CAN) JIMMY JIMMY 4.3 V6 (1999-2002)



MOTOR L35
Kapacitet: 4,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Xedoz FE 5W-30	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG
Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

DIFFERENTIALE FOR
Kapacitet: 1,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

GEAR AUTOMATISK 4L60-E 4/1
Kapacitet: 4,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 15000 km/ 12 måneder, skift alle 60000 km/ 48 måneder

GEAR MANUEL NV 3550 5/1
Kapacitet: 2 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

REDUKTIONSGEARKASSE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2032		

GMC (USA / CAN) JIMMY JIMMY 4.3 V6 (1999-2002)



SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 30000 km/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
ATF Almirol	ATF Dexron II-D	

Kontroller alle 15000 km/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
HT Q9 High Grade Grease	Labora Grease	

Skift alle 15000 km/ 12 måneder

GMC (USA / CAN) JIMMY JIMMY 4.3 V6 (1999-2002)



KØLESYSTEM

Kapacitet: 11,1 liter (med automatisk kraftoverføring), Kapacitet: 11,3 liter (med manuel transmission)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 60000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.