

# GMC (USA / CAN) YUKON / XL GMT922/932 YUKON DENALI 6.2 V8 AWD (2007-2007)



## MOTOR L94

Kapacitet: 5,7 liter (Servicepåfyldning)

| ANVEND          | KLIMA   |
|-----------------|---------|
| Fleksibel (max) | Moderat |

| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2   |  |
|---------------------------|-----------------------|--|
| <b>Presteza MSP 5W-30</b> | <b>Xedoz FE 5W-30</b> |  |

Skift alle 12 måneder

## DIFFERENTIALE BAG

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       |  |
|---------------------|---------------------------|--|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |  |

## DIFFERENTIALE FOR (4x4)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       |  |
|---------------------|---------------------------|--|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |  |

## GEAR AUTOMATISK 6L80-E 6/1

Kapacitet: 5,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 4036</b> |  |  |

Kontroller alle 12 måneder, skift alle 100000 mil

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 4036</b> |  |  |

Kontroller alle 12 måneder, skift alle 50000 mil

# GMC (USA / CAN) YUKON / XL GMT922/932 YUKON DENALI 6.2 V8 AWD (2007-2007)



## REDUKTIONSGEARKASSE (4X4)

Kapacitet: 1,4 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>ATF Almirol</b>  |  |  |

Skift alle 100000 mil

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>ATF Almirol</b>  |  |  |

Skift alle 50000 mil

## HYDRAULISK BREMSESYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Drauliquid DOT 3</b> |  |  |

## SERVOSTYRING

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

## KØLESYSTEM

Kapacitet: 17,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2   |  |
|----------------------|-----------------------|--|
| <b>Coolant SP 15</b> | <b>Coolant SP 15+</b> |  |

Kontroller alle 12 måneder, skift alle 150000 mil/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.