## GMC (USA / CAN) YUKON / XL GMT922/932 YUKON 1500 6.0 V8 HYBRID (2008-2010)



ENGINE LFA Capacity: 5,7 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Presteza MSP 5W-30	Xedoz FE 5W-30		
Change every 12 months		·	

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 1,43-1,73 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	

<b>DIFFERENTIAL REAR</b> Capacity: 2,03-2,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

Capacity: 1,4-1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 100000 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 50000 miles	

**TRANSFERBOX (4X4)** 

## GMC (USA / CAN) YUKON / XL GMT922/932 YUKON 1500 6.0 V8 HYBRID (2008-2010)



TRANSMISSION HYBRID 2ML70 - M99 4/1 Capacity: 10,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 12 months, change every 100000 miles			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 12 months, change every 50000 miles			

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 12 months, change every 24 months		

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

COOLING SYSTEM ENGINE Capacity: 14,7-17,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months, change ev	very 150000 miles/ 60 months	

## GMC (USA / CAN) YUKON / XL GMT922/932 YUKON 1500 6.0 V8 HYBRID (2008-2010)



COOLING SYSTEM POWER ELECTRONICS Capacity: 2,7-3,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.