GMC (USA / CAN) YUKON / XL GMT922/932 YUKON 6.0 V8 (2013-2014)



ENGINE L96 E85 Capacity: 5,7 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Change every 7500 miles / 12 months	

DIFFERENTIAL FRONT (4x4)

USE

Normal

Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

SP Gear 1011 Syngear TDL 75W-90

DIFFERENTIAL REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

TRANSFERBOX (4X4) Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Change every 97500 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Change every 45000 miles		

GMC (USA / CAN) YUKON / XL GMT922/932 YUKON 6.0 V8 (2013-2014)



TRANSMISSION AUTOMATIC 6L90-E 6/Capacity: 6 liter (Service fill)	1
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 97500 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 45000 miles	
·	-

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 12 months, change every 24 months	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

COOLING SYSTEM Capacity: 16,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Charles and 12 months shangs as	150000 miles/00 menths		

Check every 12 months, change every 150000 miles/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.