

HONDA (EU) JAZZ II GE GG JAZZ 1.2 I-VTEC (2008-2011)



MOTOR L12B1/L12B2

Kapacitet: 4,2 liter (Førstegangsupfyldning), Kapacitet: 3,6 liter (Servicepåfyldning), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 0W-20	Presteza MSP 0W-30	Duranza LSP 5W-30

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 0W-20	Presteza MSP 0W-30	Duranza LSP 5W-30

Skift alle 10000 km/ 6 måneder

TRANSAXSEL MANUEL 5/1

Kapacitet: 1,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 20000 km/ 12 måneder, skift alle 120000 km/ 96 måneder

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 20000 km/ 12 måneder, skift alle 36 måneder

KØLESYSTEM

Kapacitet: 4,2-4,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 20000 km/ 12 måneder, skift alle 100000 km/ 60 måneder

AIRCONDITION

Kapacitet: 370-420 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HONDA (EU) JAZZ II GE GG JAZZ 1.2 I-VTEC (2008-2011)



KLIMAANLÆGSKOMPRESSOR

Kapacitet: 80 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.