

HONDA (EU) PRELUDE PRELUDE 2.3I (1992-1996)



MOTOR H23A2

Kapacitet: 4,3 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 5000 km/ 3 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 5000 km/ 3 måneder

TRANSAKSEL AUTOMATISK 4/1

Kapacitet: 2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 40000 km/ 48 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

HONDA (EU) PRELUDE PRELUDE 2.3I (1992-1996)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Skift alle 40000 km/ 48 måneder		

SERVOSTYRING

Kapacitet: 1,7 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM

Kapacitet: 3,7 liter (+ automatisk transmission/transaksel), Kapacitet: 4 liter (+ manuel transmission/transaksel)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		
Skift alle 40000 km/ 48 måneder		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.