

# HONDA (EU) ACCORD V CC/CD/CE/CF

## ACCORD 2.0i (1996-1998)

**ENGINE F20Z1**

Capacity: 3,8 liter, Filter capacity: 0,3 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Check every 3000 km, change every 10000 km/ 12 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Check every 3000 km, change every 10000 km/ 12 months*

## USE

Severe

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 5000 km/ 6 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 5000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 2,4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol**

## PRODUCT RECOMMENDATION 3

**ATF Dexron II-D***Check every 40000 km/ 24 months, change every 80000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,9 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015***Check every 40000 km/ 24 months, change every 80000 km/ 48 months*

# HONDA (EU) ACCORD V CC/CD/CE/CF

## ACCORD 2.0i (1996-1998)



### HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Change every 60000 km/ 36 months*

### POWER STEERING

Capacity: 1,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Change every 80000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*