PRODUCT RECOMMENDATION

HONDA (EU) ACCORD VII CL/CM/CP
ACCORD 2.0I (2003-2005)

ENGINE K20A6
Capacity: 5,3 liter (Initial fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Presteza MSP 0W-20	**Duranza ECO 5W-20**	**Presteza MSP 0W-30**

Change every 20000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Presteza MSP 0W-20	**Duranza ECO 5W-20**	**Presteza MSP 0W-30**

Change every 10000 km/ 6 months

TRANSAXLE AUTOMATIC 5/1
Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months, change every 80000 km/ 48 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 40000 km/ 48 months

TRANSAXLE MANUAL 5/1
Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 20000 km/ 12 months, change every 120000 km/ 96 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HONDA (EU) ACCORD VII CL/CM/CP
ACCORD 2.0I (2003-2005)

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 20000 km/ 12 months, change every 36 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 20000 km/ 12 months, change every 36 months

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 4,5 liter (+ manual transmission/transaxle), Capacity: 4,4 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 200000 km/ 120 months

AIRCONDITIONING

Capacity: 500-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367