

HONDA (EU) CIVIC VIII FA/FD/FK/FN CIVIC

1.8I-VTEC (2008-2012)

**ENGINE R18A2**

Capacity: 4,5 liter (Dry fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|---------------------------|--------------------------|
| Presteza MSP 0W-20 | Presteza MSP 0W-30 | Duranza LSP 5W-30 |

Change every 20000 km/ 12 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|---------------------------|--------------------------|
| Presteza MSP 0W-20 | Presteza MSP 0W-30 | Duranza LSP 5W-30 |

*Change every 10000 km/ 6 months***TRANSAXLE MANUAL 6/1**

Capacity: 1,6 liter (Dry fill), Capacity: 1,4 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 5015 | | |

*Check every 20000 km/ 12 months, change every 120000 km/ 96 months***TRANSAXLE SEMI-AUTOMATIC I-Shift 6/1**

Capacity: 1,6 liter (Dry fill), Capacity: 1,4 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 5015 | | |

*Check every 20000 km/ 12 months, change every 120000 km/ 96 months***HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Check every 20000 km/ 12 months, change every 36 months

HONDA (EU) CIVIC VIII FA/FD/FK/FN CIVIC

1.8I-VTEC (2008-2012)



HYDRAULIC CLUTCH SYSTEM

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 6,8 liter (Dry fill), Capacity: 5,3 liter (Service fill)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Check every 20000 km/ 12 months, change every 200000 km/ 120 months

AIRCONDITIONING

Capacity: 440-490 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 75 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.