HONDA (EU) CIVIC VIII FA/FD/FK/FN CIVIC 2.2I-CDTI (2008-2012)



ENGINE N22A2 Capacity: 6,8 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,4 liter				
use Normal		climate Moderate		
				PRODUCT RECOMMENDATION 1
Presteza MSP 0W-30	Duranza LSP 5W-30	Helar 0W-40		
Change every 20000 km/ 12 months)			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 0W-30	Duranza LSP 5W-30	Helar 0W-40		
Change every 10000 km/ 6 months				

TRANSAXLE MANUAL 6/1 Capacity: 2,5 liter (Dry fill), Capacity: 2,2 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Gear 5015				

Check every 20000 km/12 months, change every 120000 km/96 months

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Check every 20000 km/ 12 months, ch	ange every 36 months	'		

HONDA (EU) CIVIC VIII FA/FD/FK/FN CIVIC 2.2I-CDTI (2008-2012)



COOLING SYSTEM Capacity: 7,8 liter (Dry fill), Capacity: 6,6 liter (Service fill)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1					
Coolant SP 14+					
Check every 20000 km/ 12 months, change every 60000 km/ 36 months					
USE		CLIMATE			
First change only		Moderate			
PRODUCT RECOMMENDATION 1					
PRODUCT RECOMMENDATION I					
Coolant SP 14+					

AIRCONDITIONING

Capacity: 440-490 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 75 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.