# HONDA (EU) CIVIC HYBRID FD3 CIVIC HYBRID (2005-2007)



ENGINE LDA2 Capacity: 3,2-3,6 liter (Service fill), Filt	er capacity: 0,2 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza LSP 5W-30	Helar 0W-40
Change every 20000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza LSP 5W-30	Helar 0W-40
Change every 10000 km/ 6 months		

### TRANSAXLE CVT 1/1

Capacity: 5,1 liter (Initial fill), Capacity: 2,8 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	

Check every 20000 km/ 12 months, change every 36 months

COOLING SYSTEM Capacity: 6 liter (Initial fill), Capacity: 4,75 liter (Service fill)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 20000 km/ 12 months, chang	every 100000 km/ 60 months		
USE	CLIMATE		
First change only	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 20000 km/ 12 months, chang	every 200000 km/ 120 months		

## **AIRCONDITIONING**

Capacity: 400-450 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

## HONDA (EU) CIVIC HYBRID FD3 CIVIC HYBRID (2005-2007)



### AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.