

**HONDA (EU) CIVIC III****AG/AH/AJ/AK/AL/AM/AU CIVIC 1.2 (1985-1987)****ENGINE ZA**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	<b>HDX 20W-50</b>

*Change every 10000 km/ 6 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Change every 10000 km/ 6 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	<b>HDX 20W-50</b>

*Change every 5000 km/ 3 months*

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Change every 5000 km/ 3 months***TRANSAXLE MANUAL 4/1**

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 40000 km/ 48 months*

## PRODUCT RECOMMENDATION

**HONDA (EU) CIVIC III****AG/AH/AJ/AK/AL/AM/AU CIVIC 1.2 (1985-1987)****COOLING SYSTEM**

Capacity: 4,4-4,9 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 40000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*