

# HONDA (EU) CIVIC IV EC/ED/EE CIVIC 1.6i

## VTEC (1989-1991)

**ENGINE B16A1**

Capacity: 4 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 3

**HDX 20W-50***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 10000 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 5000 km/ 3 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 3

**HDX 20W-50***Change every 5000 km/ 3 months*

USE	CLIMATE
Severe	Arctic

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 5000 km/ 3 months*

# HONDA (EU) CIVIC IV EC/ED/EE CIVIC 1.6I

## VTEC (1989-1991)



### TRANSAXLE MANUAL 5/1

Capacity: 2,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Change every 40000 km/ 48 months

### POWER STEERING

Capacity: 1,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### GREASE POINTS/NIPPLES SHIFT LEVERS

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.