PRODUCT RECOMMENDATION

HONDA (EU) PRELUDE PRELUDE 2.0I (1996-2001)

ENGINE F20A4
Capacity: 3,8 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Check every 3000 km, change every 10000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	**Emperol 10W-40**	**Bi-Turbo 15W-40**

Check every 3000 km, change every 10000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	**Emperol 10W-40**	**Bi-Turbo 15W-40**

Change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC 4/1
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Check every 40000 km/ 24 months, change every 80000 km/ 48 months

TRANSAXLE MANUAL 5/1
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 40000 km/ 24 months, change every 80000 km/ 48 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HONDA (EU) PRELUDE PRELUDE 2.0I (1996-2001)

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 60000 km/ 36 months

POWER STEERING

Capacity: 1,2 liter (Initial fill), Capacity: 0,4 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 6,9 liter (Initial fill), Capacity: 3,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367