

HONDA (EU) PRELUDE PRELUDE 2.2i (1996-2001)

**ENGINE F22Z5**

Capacity: 3,8 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 5000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 40000 km/ 24 months, change every 80000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 40000 km/ 24 months, change every 80000 km/ 48 months*

HONDA (EU) PRELUDE PRELUDE 2.2i (1996-2001)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 60000 km/ 36 months

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 3,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.