

HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT 1.6I MC (2006-2009)



MOTOR G4ED

Kapacitet: 3,3 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK A4AF3 4/1

Kapacitet: 6,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder

TRANSAKSEL MANUEL M5CF1 5/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Skift alle 45000 km/ 36 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 24 måneder

HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT 1.6I MC (2006-2009)

**SERVOSTYRING**

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D**SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2**KØLESYSTEM**

Kapacitet: 5,5-5,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF*Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.