

HYUNDAI (EU) I10 IA I10 1.2 MPI (2014-2018)



MOTOR Kappa 16V

Kapacitet: 3,5 liter (Servicepåfyldning), Kapacitet: 3,55 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK A4CF0 4/1

Kapacitet: 6,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 60000 km/ 48 måneder, skift alle 100000 km

TRANSAKSEL MANUEL M5EF2 5/1

Kapacitet: 1,9-2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 60000 km/ 48 måneder, skift alle 120000 km



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 35000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 5,2 liter (med automatisk kraftoverføring), Kapacitet: 5,3 liter (med manuel transmission)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 40000 km/ 24 måneder

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 210000 km/ 120 måneder

KLIMAANLÆGSSYSTEM R-1234yf

Kapacitet: 375-425 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 375-425 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.