

HYUNDAI (EU) I10 PA I10 1.0 D-CVVT (2011-2013)



MOTOR Kappa
Kapacitet: 2,7 liter (Servicepåfyldning), Kapacitet: 3,15 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Bi-Turbo 20W-50

Skift alle 20000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Duranza LSP 5W-30

Skift alle 20000 km

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Bi-Turbo 20W-50

Skift alle 15000 km

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Duranza LSP 5W-30

Skift alle 15000 km

TRANSAKSEL AUTOMATISK A4CF0 4/1
Kapacitet: 6,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 20000 km, skift alle 115000 km

TRANSAKSEL MANUEL M5EF2 5/1
Kapacitet: 1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

HYUNDAI (EU) I10 PA I10 1.0 D-CVVT (2011-2013)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 20000 km

KØLESYSTEM

Kapacitet: 3,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 20000 km, skift alle 55000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.