

HYUNDAI (EU) I40 VF I40 1.7 CRDI (104 KW) (2015-2017)



MOTOR D4FD

Kapacitet: 5,3 liter (Servicepåfyldning), Kapacitet: 5,7 liter (Tør efterfyld), Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK A6MF2 6/1

Kapacitet: 7,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
SP Matic 4036	

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
SP Matic 4036	

Kontroller alle 60000 km/ 48 måneder, skift alle 90000 km

TRANSAKSEL HALVAUTOMATISK D7UF1 7/1

Kapacitet: 1,9-2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
SP Gear 1081	

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
SP Gear 1081	

Kontroller alle 60000 km/ 48 måneder, skift alle 90000 km

HYUNDAI (EU) I40 VF I40 1.7 CRDI (104 KW) (2015-2017)



TRANSAKSEL MANUEL M6GF2 6/1

Kapacitet: 1,8-2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 60000 km/ 48 måneder, skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 6,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 525-575 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.