

HYUNDAI (EU) I800 TQ I800 2.5 CRDI VGT (125 KW) (2007-2009)



MOTOR A2.5
Kapacitet: 7,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40

Skift alle 7500 km/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 1,8-2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-4 80W-90		

Kontroller alle 24 måneder/ 30000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-4 80W-90		

Skift alle 90000 km

GEAR AUTOMATISK A5SR1 5/1
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 15000 km/ 12 måneder, skift alle 90000 km/ 72 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Skift alle 40000 km

HYUNDAI (EU) I800 TQ I800 2.5 CRDI VGT (125 KW) (2007-2009)



GEAR MANUEL 6/1

Kapacitet: 3,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Skift alle 100000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 0,9-1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 15000 km/ 12 måneder

HYUNDAI (EU) I800 TQ I800 2.5 CRDI VGT (125 KW) (2007-2009)



KØLESYSTEM

Kapacitet: 10-13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 40000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 100000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.