

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (85 KW) (2009-2019)



MOTOR A2.5
Kapacitet: 7,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Skift alle 10000 km/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 1,8-2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube GL-4 80W-90	

Kontroller alle 40000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
Gearlube GL-4 80W-90	

Skift alle 80000 km

GEAR AUTOMATISK A5SR1 5/1
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
SP Matic 4026	

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
SP Matic 4026	

Skift alle 90000 km

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (85 KW) (2009-2019)



GEAR MANUEL 6/1 Kapacitet: 3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM Kapacitet: 0,7-0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

SERVOSTYRING Kapacitet: 0,9-1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 20000 km/ 12 måneder

HYUNDAI (EU) I800 TQ I800 2.5 CRDI WGT (85 KW) (2009-2019)

**KØLESYSTEM**

Kapacitet: 10-13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Skift alle 30000 km/ 24 måneder*

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Skift alle 210000 km/ 120 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.