

HYUNDAI (EU) I800 TQ I800 2.5 TCI (2009-2019)



MOTOR D4BH/4D56
Kapacitet: 5,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Asyntho 5W-30	Bi-Turbo 15W-40

Skift alle 3000 km/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 1,8-2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube GL-4 80W-90	

Kontroller alle 24 måneder/ 30000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
Gearlube GL-4 80W-90	

Skift alle 90000 km

GEAR AUTOMATISK 4/1
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
SP Matic 4026	

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
SP Matic 4026	

Skift alle 90000 km

HYUNDAI (EU) I800 TQ I800 2.5 TCI (2009-2019)



GEAR MANUEL 5/1

Kapacitet: 1,95 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 48 måneder/ 60000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 0,9-1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

HYUNDAI (EU) I800 TQ I800 2.5 TCI (2009-2019)



KØLESYSTEM

Kapacitet: 10-13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 30000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 210000 km/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.