

HYUNDAI (EU) IX20 JC IX20 1.4 CRDI DPF (2015-2018)



MOTOR (U-SERIE) D4FC

Kapacitet: 5,3 liter (Servicepåfyldning), Kapacitet: 5,7 liter (Tør efterfyld), Filterkapacitet: 0,5 liter

ANVEND		KLIMA
Foretrukne		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Helar SP LL-03 0W-30

Kontroller alle 500 km, skift alle 30000 km/ 24 måneder

ANVEND		KLIMA
Stærk (foretrukket)		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Helar SP LL-03 0W-30

Skift alle 15000 km/ 12 måneder

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 5W-30	Presteza MSP 5W-30	

Kontroller alle 500 km, skift alle 20000 km/ 12 måneder

ANVEND		KLIMA
Alternativ, svær		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 5W-30	Presteza MSP 5W-30	

Skift alle 10000 km/ 6 måneder

TRANSAKSEL MANUEL M6CF3-1 6/1

Kapacitet: 1,9-2 liter

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 48 måneder/ 60000 km

ANVEND		KLIMA
Krævende		Moderat

PRODUKTANBEFALING 1		
SP Gear 1081		

Skift alle 120000 km

HYUNDAI (EU) IX20 JC IX20 1.4 CRDI DPF (2015-2018)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 6,4-6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 30000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 90-110 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 525-575 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.