

HYUNDAI (EU) IX35 / TUCSON EL/LM IX35 2.0 GDI 2WD (2014-2014)



MOTOR Nu

Kapacitet: 4 liter (Servicepåfyldning), Kapacitet: 4,5 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza LSP 5W-30

PRODUKTANBEFALING 2

Emperol 5W-40

Kontroller alle 500 km, skift alle 30000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza LSP 5W-30

PRODUKTANBEFALING 2

Emperol 5W-40

Kontroller alle 500 km, skift alle 15000 km/ 6 måneder

TRANSAKSEL AUTOMATISK A6MF1 6/1

Kapacitet: 7,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Skift alle 100000 km

TRANSAKSEL MANUEL M6CF4 6/1

Kapacitet: 2,1-2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 60000 km/ 24 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 60000 km/ 24 måneder, skift alle 120000 km

HYUNDAI (EU) IX35 / TUCSON EL/LM IX35 2.0 GDI 2WD (2014-2014)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 6,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 30000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder

KLIMAANLÆGSKOMPRESSOR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 485-535 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.