

HYUNDAI (EU) LANTRA / ELANTRA J1

LANTRA / ELANTRA 1.5I (1991-1992)



MOTOR

Kapacitet: 3 liter, Filterkapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Classic Racing Oil 15W-50

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 10000 km/ 6 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 10000 km/ 6 måneder

TRANSAKSEL AUTOMATISK 4/1

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 40000 km/ 48 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km, skift alle 40000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 80000 km/ 24 måneder

HYUNDAI (EU) LANTRA / ELANTRA J1

LANTRA / ELANTRA 1.5i (1991-1992)



SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 40000 km/ 48 måneder

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 5,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 50000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.