

HYUNDAI (EU) LANTRA/ ELANTRA RD/J2

LANTRA / ELANTRA 1.5I (1995-2000)



MOTOR Alpha
Kapacitet: 3 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK 4/1
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Skift alle 30000 km/ 24 måneder

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Skift alle 30000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 30000 km/ 24 måneder

HYUNDAI (EU) LANTRA/ ELANTRA RD/J2

LANTRA / ELANTRA 1.5I (1995-2000)



SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 45000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.