

# HYUNDAI (EU) MATRIX FC MATRIX 1.5 CRDI VGT (81 KW) (2004-2008)



**MOTOR D4FA**  
Kapacitet: 5,3 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Asyntho 5W-30**

PRODUKTANBEFALING 2

**Bi-Turbo 15W-40**

*Skift alle 15000 km/ 12 måneder*

**TRANSAKSEL AUTOMATISK A4BF2 4/1**  
Kapacitet: 6,1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**SP Matic 4026**

*Kontroller alle 15000 km/ 12 måneder, skift alle 60000 km/ 48 måneder*

**TRANSAKSEL MANUEL M5BF2 5/1**  
Kapacitet: 2,15 liter

ANVEND  
->2005

KLIMA  
Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

PRODUKTANBEFALING 3

**Syngear 75W-90**

*Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder*

ANVEND  
2005->

KLIMA  
Moderat

PRODUKTANBEFALING 1

**SP Gear 5015**

PRODUKTANBEFALING 2

**Syngear 75W-90**

*Kontroller alle 15000 km/ 12 måneder*

**HYDRAULISK BREMSESYSTEM ABS**  
Kapacitet: 1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

PRODUKTANBEFALING 3

**Drauliquid DOT 3**

*Kontroller alle 15000 km/ 12 måneder, skift alle 120000 km/ 24 måneder*

# HYUNDAI (EU) MATRIX FC MATRIX 1.5 CRDI VGT (81 KW) (2004-2008)



## SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D**

*Kontroller alle 15000 km/ 12 måneder*

## KØLESYSTEM

Kapacitet: 6,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

*Kontroller alle 15000 km/ 12 måneder, skift alle 36 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*