

HYUNDAI (EU) MATRIX FC MATRIX 1.6i (2008-2010)



MOTOR G4ED

Kapacitet: 3,3 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK A4AF3 4/1

Kapacitet: 6,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 15000 km/ 12 måneder, skift alle 60000 km/ 48 måneder

TRANSAKSEL MANUEL M5BF2 5/1

Kapacitet: 2,15 liter

ANVEND

->2005

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder

ANVEND

2005->

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

HYUNDAI (EU) MATRIX FC MATRIX 1.6I (2008-2010)



HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 120000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 15000 km/ 12 måneder, skift alle 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.