

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2 CRDI VGT (2012-2014)



MOTOR (R-SERIE)

Kapacitet: 6,3-6,7 liter (Servicepåfyldning), Kapacitet: 7,3-7,8 liter (Tør efterfyld), Filterkapacitet: 0,7 liter

ANVEND	KLIMA
Normal, Brændstof i henhold til EN 590	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Normal, Brændstof i henhold til EN 590	Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Asyntho 5W-30

Kontroller alle 500 km, skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Asyntho 5W-30

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK A6LF3 6/1

Kapacitet: 7,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Skift alle 90000 km

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2 CRDI VGT (2012-2014)



TRANSAKSEL MANUEL M6LF1 6/1

Kapacitet: 1,8-1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 48 måneder/ 60000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 60000 km/ 48 måneder, skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 24 måneder/ 30000 km

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2

CRDI VGT (2012-2014)

**KØLESYSTEM**

Kapacitet: 9,1-9,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Skift alle 30000 km/ 24 måneder*

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.