

HYUNDAI (EU) TERRACAN HP TERRACAN 2.9 CRDI (2001-2007)



MOTOR J3

Kapacitet: 7,5 liter (Førstegangsupfyldning), Kapacitet: 6 liter (Servicepåfyldning), Filterkapacitet: 0,63 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG 4x4

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Kontroller alle 15000 km/ 12 måneder

DIFFERENTIALE FOR

Kapacitet: 1,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Kontroller alle 15000 km/ 12 måneder

REDUKTIONSGEARKASSE

Kapacitet: 1,42 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 15000 km/ 12 måneder

HYUNDAI (EU) TERRACAN HP TERRACAN 2.9 CRDI (2001-2007)



TRANSAKSEL AUTOMATISK F4A42-1/2 4/1

Kapacitet: 10,46 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

ATF Dexron II-D

Kontroller alle 30000 km/ 24 måneder, skift alle 90000 km/ 72 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,5-3,2 liter

ANVEND

->2005

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

ANVEND

2005->

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

HYUNDAI (EU) TERRACAN HP TERRACAN 2.9 CRDI (2001-2007)



KØLESYSTEM

Kapacitet: 9,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.