
HYUNDAI (USA) AZERA TG AZERA 3.8





| ENGINE Lambda Capacity: 5,2 liter | | |
|--------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 0W-20 | Duranza ECO 5W-20 | Duranza LSP 5W-30 |
| Change every 7500 miles/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 0W-20 | Duranza ECO 5W-20 | Duranza LSP 5W-30 |

| TRANSAXLE AUTOMATIC A5GF1, A5HF1 5/1 Capacity: 10,9 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |
| Check every 15000 miles/ 12 months, change every 105000 miles/ 84 months | | |
| USE | | CLIMATE |

| USE | CLIMATE |
|--------------------------|----------|
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4026 | |
| | |

Change every 30000 miles/24 months

Change every 3000 miles/ 3 months

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 | |
| Check every 30000 miles/24 months | | ' | |

HYUNDAI (USA) AZERA TG AZERA 3.8 (2007-2010)



Check every 15000 miles/ 12 months

SP Fluid 3013

| COOLING SYSTEM Capacity: 8,3 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 30000 miles/24 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 60000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.